



Small, compact industrial glands with armour termination, suitable for internal applications, not recommended for installation outdoors.

Designed for use with SWA and similar single wire armoured cables where there is a need for clamping the armour for electrical continuity and/or mechanical retention purposes.

Supplied complete with earth tag, locknut & shroud as standard, also available with LSF shrouds to complement halogen free cables on request.

### Construction

high quality brass body

two part armour / earth lock

low resistance earth clamp

IP54 ingress protection rating; protected against dust, limited ingress permitted (no harmful deposit), protected against light water sprays from all directions, limited ingress permitted.

stainless steel & nickle plated versions may be available on request.

Gland Size (reference)	Thread Size (mm)	Maximum Cable Diameter (mm)	
		under armour	overall
BW-20s	20	11.6	16.1
BW-20	20	13.9	21.1
BW-25	25	19.9	27.4
BW-32	32	26.2	34.4
BW-40	40	32.1	42.4
BW-50s	50	38.1	50.1
BW-50	50	44.0	55.7
BW-63s	63	50.0	62.4
BW-63	63	55.9	68.2
BW-75s	75	61.9	76.8
BW-75	75	67.9	82.9

**For more information international Ingress Protection classification system see our "Understanding IP Ratings" page under Customer Support, Technical Information.**

**All measurements provided should be considered nominal and images for illustration purposes only. Although Central Cables Ltd has made every reasonable effort to ensure its accuracy, the information contained herein is subject to error or omission and to change without notice. In no event will Central Cables Ltd be liable for any damages whatsoever, arising in connection with the information described.**