

Class 6 conductors, stranding and resistance

The values in this chart are extracted in general terms from DIN VDE 0295 (equivalent to IEC 60228 and BS6360)

Area (mm ²)	Stranding (mm)	Resistance (Ω/km)	
		Plain Copper	Tinned Copper
0.14	18x 0.10	138.0	139.0
0.25	32x 0.10	79.0	79.1
0.34	42x 0.10	57.0	57.5
0.5	28x 0.16	39.0	40.1
0.75	42x 0.16	26.0	26.7
1.0	56x 0.16	19.5	20.0
1.5	84x 0.16	13.3	13.7
2.5	140x 0.16	7.98	8.21
4.0	224x 0.16	4.95	5.09
6.0	192x 0.21	3.30	3.39
10.0	320x 0.21	1.91	1.95
16.0	512x 0.21	1.21	1.24
25.0	800x 0.21	0.780	0.795
35.0	1120x 0.21	0.554	0.565
50.0	705x 0.31	0.386	0.393
70.0	990x 0.31	0.272	0.277
95.0	1340x 0.31	0.206	0.210
120	1690x 0.31	0.161	0.164
150	2123x 0.31	0.129	0.132
185	1470x 0.41	0.106	0.108
240	1905x 0.41	0.081	0.082

Conductor resistances shown are maximum values at 20°C.

The above strand counts show the maximum number of strands required, there may be fewer strands provided the maximum Ω/km (see resistance chart) is not exceeded.

Although Central Cables Ltd has made every reasonable effort to ensure its accuracy, the information contained herein is subject to error or omission and to change without notice. In no event will Central Cables be liable for any damages whatsoever, arising in connection with the information described.