



Flexible cables designed for measuring and control purposes in plant installations, tool machinery, conveyor belts, production lines, air conditioning systems, steel production plants and rolling mills.

Suitable for internal or external applications in dry, moist or wet areas. Not recommended for direct burial or underwater installation.

**Construction**

- fine stranded plain copper conductors
- polyvinylchloride (PVC) core insulation
- cores twisted in layers
- black oil resistant PVC outer sheath

**Technical**

conductor stranding:	according to class 5 (VDE 0295 / IEC 60228 / BS EN 60228:2005)
bend radius:	4 x overall diameter (O/D) fixed, 15 x O/D flexing
voltage rating:	600/1000V operating, 4000V test
current rating:	see YY, SY & CY derivative chart
temperature range:	-5°C to +80°C flexible, -40°C to +80°C static
standards:	construction generally to VDE 0262/12.95 and VDE 0281 part 13
	flame retardant according to IEC 60332-1
	oil resistant according to EN 60811-2-11
core identification:	OZ, usually 2 core = numbered black cores without earth (green/yellow)
	NR, usually 3+ cores = numbered black cores with earth (inc. in core count)

Number of Cores	Conductor Area (mm <sup>2</sup> )	Overall Diameter (mm)	Overall Weight (kg/km)	Number of Cores	Conductor Area (mm <sup>2</sup> )	Overall Diameter (mm)	Overall Weight (kg/km)
2	0.5	6.3	55	3	0.75	7.5	91
3	0.5	6.7	76	4	0.75	7.9	120
4	0.5	7.3	100	5	0.75	8.7	134
5	0.5	8.0	116	7	0.75	9.8	177
7	0.5	9.0	136	12	0.75	12.7	248
12	0.5	11.6	200	18	0.75	14.9	350
18	0.5	14.0	283	25	0.75	17.7	477
25	0.5	16.6	389	34	0.75	21.5	626
				41	0.75	23.1	733
2	0.75	6.8	63	50	0.75	25.3	871

Number of Cores	Conductor Area (mm <sup>2</sup> )	Overall Diameter (mm)	Overall Weight (kg/km)	Number of Cores	Conductor Area (mm <sup>2</sup> )	Overall Diameter (mm)	Overall Weight (kg/km)
2	1.0	7.4	73	3	4.0	12.6	225
3	1.0	7.6	98	4	4.0	14.0	314
4	1.0	8.2	110	5	4.0	15.3	403
5	1.0	9.6	138	7	4.0	16.7	524
7	1.0	10.6	179				
12	1.0	13.7	281	3	6.0	14.2	365
18	1.0	16.0	408	4	6.0	15.7	428
25	1.0	19.4	567	5	6.0	17.9	602
34	1.0	23.5	764	7	6.0	19.7	802
41	1.0	25.6	891				
50	1.0	26.8	1076	4	10.0	18.5	759
				5	10.0	20.5	927
2	1.5	8.5	99	7	10.0	23.0	1293
3	1.5	9.2	122				
4	1.5	9.9	150	4	16.0	21.9	1101
5	1.5	11.1	176	5	16.0	25.6	1617
7	1.5	12.0	220	7	16.0	27.1	1873
12	1.5	15.8	411				
18	1.5	19.0	547	4	25.0	27.2	1624
25	1.5	22.8	771	5	25.0	29.5	2074
34	1.5	26.6	996	7	25.0	33.0	2946
50	1.5	30.4	1427				
				4	35.0	29.8	2403
2	2.5	9.8	142	5	35.0	33.5	2987
3	2.5	10.4	176				
4	2.5	11.5	224	4	50.0	37.1	3402
5	2.5	12.8	253				
7	2.5	15.2	337	4	70.0	41.9	4354
12	2.5	18.2	551				
18	2.5	21.7	790	4	95.0	48.4	6012
25	2.5	26.0	1101				
				4	120.0	53.8	7503

**PVC properties:** fairly tough & flexible material with fair abrasive resistance, good resistance to water, aqueous salt solutions, acids and alkalis, moderate/poor resistance against organic solvents and oils. Oil resistant PVC (polyvinylchloride) is commonly available.

All measurements provided should be considered nominal and images for illustration purposes only. Although Central Cables Ltd has made every reasonable effort to ensure its accuracy, the information contained herein is subject to error or omission and to change without notice. In no event will Central Cables Ltd be liable for any damages whatsoever, arising in connection with the information described.