



Designed for flexible connecting, measuring, checking and control applications in the machine, plant and tool making industries.

These tough sheathed cables are suitable for installation indoors or outdoors, in dry, moist or wet areas and where exposed to harsh mechanical strain or dragged over sharp/rough surfaces.

Construction

fine stranded plain copper conductors
 polyvinylchloride (PVC) core insulation
 cores twisted in layers
 grey polyurethane (PUR) outer sheath

<u>Technical</u>	
conductor stranding:	according to class 5 (VDE 0295 / IEC 60228 / BS EN 60228:2005)
bend radius:	4 x overall diameter (O/D) fixed, 15 x O/D flexing
voltage rating:	300/500V operating, 4000V test
current rating:	see YY, SY & CY derivative chart
insulation resistance:	20 MOhm/km maximum @ 20°C
temperature range:	-5°C to +70°C flexible, -40°C to +80°C static
standards:	construction generally to BS6500 & VDE0250
	flame retardant according to IEC 60332-1
	oil resistant according to VDE 0472 part 803, VDE 0285
core identification:	OZ, usually 2 core = numbered black cores without earth (green/yellow)
	NR, usually 3+ cores = numbered black cores with earth (inc. in core count)

Number of Cores	Conductor Area (mm ²)	Overall Diameter (mm)	Overall Weight (kg/km)	Number of Cores	Conductor Area (mm ²)	Overall Diameter (mm)	Overall Weight (kg/km)
2	0.5	5.0	32	34	0.5	15.2	333
3	0.5	5.3	43	41	0.5	16.6	400
4	0.5	5.7	50				
5	0.5	6.5	59	2	0.75	5.9	41
7	0.5	7.0	73	3	0.75	6.2	51
10	0.5	9.0	109	4	0.75	7.2	62
12	0.5	9.5	125	5	0.75	7.8	74
18	0.5	11.2	180	7	0.75	8.5	97
25	0.5	13.5	250	9	0.75	10.6	124

Number of Cores	Conductor Area (mm ²)	Overall Diameter (mm)	Overall Weight (kg/km)	Number of Cores	Conductor Area (mm ²)	Overall Diameter (mm)	Overall Weight (kg/km)
12	0.75	11.2	163	3	2.5	10.0	132
18	0.75	13.2	234	4	2.5	11.1	163
25	0.75	16.0	324	5	2.5	12.2	186
34	0.75	16.8	431	7	2.5	13.7	267
41	0.75	18.3	529	12	2.5	17.6	445
2	1.0	5.8	48	4	4.0	12.4	237
3	1.0	7.5	61	5	4.0	13.8	291
4	1.0	8.1	74	4	6.0	14.1	327
5	1.0	9.3	89	5	6.0	15.8	424
7	1.0	10.1	116	4	10.0	17.8	567
12	1.0	12.9	197	5	10.0	19.9	695
18	1.0	15.3	289	4	16.0	20.6	1052
25	1.0	18.4	412	5	16.0	23.6	1400
34	1.0	19.0	532	4	25.0	29.4	1590
41	1.0	20.1	638	4	35.0	32.8	2200
2	1.5	6.2	69	4	50.0	38.9	2400
3	1.5	7.9	79	4	70.0	44.7	4400
4	1.5	8.8	98	4	95.0	59.6	6000
5	1.5	9.9	121				
7	1.5	10.7	159				
12	1.5	13.6	268				
18	1.5	16.3	392				
25	1.5	20.0	531				
34	1.5	22.2	722				
41	1.5	24.1	867				

PUR Properties: UV resistant material with excellent abrasion and tear resistance. Good resistance to water and mineral oils. Poor resistance to acids, alkalis and organic solvents.

All measurements provided should be considered nominal and images for illustration purposes only. Although Central Cables Ltd has made every reasonable effort to ensure its accuracy, the information contained herein is subject to error or omission and to change without notice. In no event will Central Cables Ltd be liable for any damages whatsoever, arising in connection with the information described.