



Flexible cables for connecting, measuring, checking and control applications, the armour provides protection against mechanical damage. Suitable for use in internal, external or ducted applications.

LSZH cables ensure increased safety in the case of fire due to the virtual elimination of toxic fumes if burnt. Pronounced advantages when compared to PVC cabling: low fire load, low smoke emission, reduced fire propagation.

**Construction**

- stranded plain copper conductors
- low smoke zero halogen (LSZH) core insulation
- cores twisted together, LSZH bedding
- galvanised steel wire braid (GSWB) screen
- black LSZH outer sheath

**Technical**

conductor stranding:	according to class 5 (VDE 0295 / IEC 60228 / BS EN 60228:2005)
bend radius:	10 x overall diameter (O/D) fixed, 20 x O/D flexing
voltage rating:	300/500V operating, 2000V test
current rating:	see YY, SY & CY derivative chart
temperature range:	-5°C to +70°C flexible, -30°C to +70°C static
standards:	construction generally to BS6500 & VDE0250
	flame retardant according to IEC/EN 60332-1-2
	smoke emission according to IEC/EN 61034-2
	halogen acid gas emission according to IEC 60754-1, EN 50267-2-1
core identification:	numbered black cores with earth (included in core count)

Number of Cores	Conductor Area (mm <sup>2</sup> )	Overall Diameter (mm)	Overall Weight (kg/km)	Number of Cores	Conductor Area (mm <sup>2</sup> )	Overall Diameter (mm)	Overall Weight (kg/km)
3	1.5	9.2	140	3	2.5	10.6	220
4	1.5	9.8	180	4	2.5	11.2	260

**LSZH Properties:** fairly tough & flexible material resistant to a wide range of oils & chemicals. Guarantees max. 0.5% HCL emissions if burnt. Also known as LSOH & LSHF (low smoke zero halogen/halogen free).

Not to be confused with LSF (low smoke and fume) for which may just mean modified PVC. There is no standard governing the hydrogen chloride (HCL) emissions of LSF so it may still be hazardous if burnt.

All measurements provided should be considered nominal and images for illustration purposes only. Although Central Cables Ltd has made every reasonable effort to ensure its accuracy, the information contained herein is subject to error or omission and to change without notice. In no event will Central Cables Ltd be liable for any damages whatsoever, arising in connection with the information described.